



TESATAST Standard Models

| No | | | | | | |
|-----------|-----|-------|----|--------------|--|-------|
| 01810005 | 0,8 | 0,01 | 28 | 0 ÷ 0,4 ÷ 0 | | 12,53 |
| 01810006 | 0,8 | 0,01 | 38 | 0 ÷ 0,4 ÷ 0 | | 12,53 |
| 01810007 | 0,5 | 0,01 | 28 | 0 ÷ 0,25 ÷ 0 | | 36,53 |
| 01810008 | 0,5 | 0,01 | 38 | 0 ÷ 0,25 ÷ 0 | | 36,53 |
| 01810009 | 0,2 | 0,002 | 28 | 0 ÷ 100 ÷ 0 | | 12,53 |
| 01810010 | 0,2 | 0,002 | 38 | 0 ÷ 100 ÷ 0 | | 12,53 |
| S18001695 | 0,2 | 0,001 | 38 | 0 ÷ 100 ÷ 0 | | 12,53 |

DIN 2270
NFE 11-053

Rotating dial

Very low measuring force, see table.

Movement with patented shock proof system

Lever system with friction drive to prevent overload

Accuracy: see table.

Supplied in a plastic case together with:
1 Insert with a 2 mm dia.
1 Wrench (No. 01860307)
1 Mounting rod 8 mm dia.
(No. 01840105)



SWISSTAST Standard Models

| No | | | | | | |
|----------|-----|-------|----|-------------|--|-------|
| 01811000 | 0,8 | 0,01 | 28 | 0 ÷ 0,4 ÷ 0 | | 12,53 |
| 01811001 | 0,2 | 0,002 | 38 | 0 ÷ 100 ÷ 0 | | 12,53 |

Same technical data as standard models, but equipped with a 2 mm dia. ruby ball tip No. 01860302.

TESATAST Perpendicular Models



| No | | | | | | |
|----------|-----|------|----|--------------|--|-------|
| 01810204 | 0,8 | 0,01 | 28 | 0 ÷ 0,4 ÷ 0 | | 12,53 |
| 01810205 | 0,5 | 0,01 | 28 | 0 ÷ 0,25 ÷ 0 | | 36,53 |
| 01810304 | 0,2 | 0,01 | 38 | 0 ÷ 100 ÷ 0 | | 12,53 |

